

HALOGEN AND FLUORESCENT LIGHTS



WITH 2 BULBS

40.000 LUX

30747



30.000 LUX

CE 73/23

Length of arm +lamp 95 cm

30760




CE 93/42

CEI 62-5

30740

- **30747 SOLESUD 2 on trolley**
Halogen examination light with articulated joint arm.
- **30748 SOLESUD 2 wall**
Suitable for gynaecology, examination and head-bed. Aluminium reflector is equipped with 2 halogen dichroic bulbs, 20W 12V IRC protected by a tempered glass, hermetically sealed against dirt and fluid spray and with ergonomic handle for movement. Bulbs switch on simultaneously and, in case one breaks, light is always assured. Arm is made with articulated joint and mechanical frictions. A light beam of 180 mm diameter at a distance of 50 cm allows precise and reliable examinations. Base with 5 rotary spokes, 900 mm height. Generates a light intensity of: 40,000 lux at 50 cm. Made in Italy.
- **30769 SPARE TROLLEY**
- **30764 SPARE BULB SOLESUD 2 - 20 W**
For code 30747-8
- **30765 SPARE BULB SOLESUD - 50W**
For code 30745-6

- **30760 SIMPLEX on trolley**
Halogen examination light with flexible arm.
- **30761 SIMPLEX wall**
- **30762 SIMPLEX table with clamp**
An economic solution for your ambulatory! This lamp is equipped with a halogen dichroic bulb 35W 12V situated inside the aluminium reflector and protected by a tempered glass. Thanks to its flexible arm (700 mm long) it bends everywhere the task requires without interfering with operator's view. Supplied on a 5 castors trolley for easier mobility. Generates a light intensity of: 30,000 lux at 50 cm. Made in Italy.
- **30766 SPARE BULB SIMPLEX - IRC 35 W**
- **30768 SPARE TROLLEY**



FIXING SYSTEMS
On request we can supply all lamps with wall, table or rail (1,000 mm) connection

- **30740 SOLENORD on trolley**
Magnifying glass self-illuminating fluorescent cold light - 3 dioptries
- **30741 SOLENORD wall**
Suggested for dermatology, this model is equipped with a biconvex magnifying glass diameter 120 mm, in optical glass. The cold fluorescent light allows prolonged use. Light source protection in plexiglass. Thanks to its spring arm and to the 5 castors trolley it is very easy to change its position whenever necessary. Fluorescent circline 230 V. This light has been certified by IMQ the most important Italian notified body for certification. Made in Italy.
- **30767 SPARE FLUORESCENT LAMP - 22W**
- **30771 SPARE PLEXIGLASS SHIELD**
- **30769 SPARE TROLLEY**

ALL LIGHTS AVAILABLE ALSO AT 110 V

Model	SOLESUD 2	MINI MED	SIMPLEX	SOLENORD
Type of lighting	halogen	halogen	halogen	fluorescent
Consumption (Watt)	2x20	20	35	22
Life of the bulbs (hours)	5,000	5,000	5,000	6,000
Light intensity at 50 cm (lux)	40,000	15,000	30,000	550
Light intensity at 1 m (lux)	8,000	3,000	8,000	275
Colour temperature +/- 5% at 1 m (K)	3,000	3,000	3,000	4,550
Light field size at 50 cm (ø mm)	180	100	100	-
Dimmer	yes	no	no	no
External diameter of the reflector (ø mm)	140	70	105	230
Temperature increase at 1 m. (°C)	2	2	2	0
Colour	white	white	white	white
Norms	IEC 601-1	IEC 598-2-25	IEC 598-2-25	IEC 601-1
Marks	CE93/42	CE 73/23	CE 73/23/EEC	CE93/42 - IMQ
Weight (kg)	6	2	5	7
Operating voltage V-Hz	230 - 50/60	230	230 - 50/60	230 - 50
Adjustment height with castors base: min and max approx. cm.	60-160	60-160	60-160	60-160

- **30758 MINI MED on trolley**
Halogen examination light with flexible arm
Halogen dichroic bulb 20W 12V 15000 lux at 50 cm
Examination light equipped with a halogen dichroic bulb 20W 12V 12° and with glass protection shield. Reinforced flexible arm 70 cm length with ergonomic reflector easy to move.
- **30772 SPARE BULB MINIMED**

