

# HOT AIR STERILIZERS: GIMETTE 1.5, 7, 21, 28 AND 50 LITRES

**GIMETTE 1,5**



35601

- 35601 GIMETTE 1.5 - hot air sterilizer
- 35607 GIMETTE 7 - hot air sterilizer



Automatic Gimette are compact and high quality hot air sterilizers with the same reliability and efficiency as larger models.

Outside structure is made of painted plate with anti-scratch epoxy powder.

Stainless steel lid and sterilization chamber with approx.

Capacity of 1.5 l. and 7 l.

Removable, perforated for air circulation, tray with pliers.

All components certified by most important European brands, assembling in compliance with EN-61010.

A second safety thermostat triggers in case temperature should exceed 220°C.

Red LED indicates any anomaly in thermoregulation and consequent starting of safety thermostat.

**GIMETTE 7**



35607

## TECHNICAL SPECIFICATIONS

### GIMETTE 1,5

Inside dimensions: 245 x 120 x 50 mm = vol. 1.5 dm<sup>3</sup>

Outside dimensions: 310 x 180 x 180 mm

Power consumption: 250 Watt

Weight: 4.3 kg  
Fuse: 1 A

### GIMETTE 7

Inside dimensions: 410 x 180 x 90 mm = vol. 7 dm<sup>3</sup>

Outside dimensions: 490 x 310 x 180 mm

Power consumption: 400 Watt

Weight: 8 kg  
Fuses: 2 x 2.5 A

Thermometer: high precision with capillary bulb

Same specifications for both models:

Operating Voltage: 230 V. - 50 Hz.

Thermostat: automatic, adjustable 0-200 °C

Timer: manual from 0 to 120 minutes

2° Thermostat: bi-metallic certified

Green LED: timer, orange LED: heating, red LED: alarm

Made in Italy - Warranty 1 year

**GIMETTE 21**



35621

- 35621 GIMETTE 21 - hot air sterilizer
- 35628 GIMETTE 28 - hot air sterilizer
- 35629 GIMETTE 50 - hot air sterilizer



Fully automatic hot air sterilizer, with adjustable temperature from 0°C to 200°C, kills off even particularly resistant micro-organisms.

Stainless steel structure is powder painted, except for the door, to assure maximum heat and shock resistance over time.

Four perforated, anodized aluminium trays make hot air circulation easier.

Capacity approximately 20 l., 28 l. and 50 l.

A second safety thermostat triggers in case temperature should exceed 230°C.

Red LED indicates any anomaly in thermoregulation and consequent starting of safety thermostat.

**GIMETTE 28**



35628

## TECHNICAL SPECIFICATIONS

	GIMETTE 21	GIMETTE 28	GIMETTE 50
Inside dimensions mm:	300x250x260	380x250x260	405x340x350
Approx. volume	20 dm <sup>3</sup>	28 dm <sup>3</sup>	50 dm <sup>3</sup>
Outside dimensions mm:	440x340x400	550x340x400	605x460x480
Weight:	13 kg	17 kg	24.5 kg
Power consumption:	600 Watt	500 Watt	1200 Watt

Same specifications for 3 models:

Operating Voltage: 230 V. - 50 Hz.

Fuses: 2 x 4 A (35621, 35628) 2 x 8 A (35629)

Timer: manual from 0 to 120 minutes Thermostat: automatic

Thermometer: high precision with capillary bulb

2° Thermostat: bi-metallic certified

Green LED: timer, orange LED: heating, red LED: alarm

Made in Italy - Warranty 1 year

User/Service manual in Italian, English, Spanish