

SENATOR LOW VACUUM

Reliability and Safety

The suction pump with especially low noise levels for all procedures where low vacuum is required.

What is **SENATOR LOW VACUUM** ?

- Suction capacity of 15 liters/minute
- Rapid vacuum creation of up to 100mbar (10kPa)
- Especially low noise and vibration levels
- Maintenance-free 2-cylinder piston system
- Straightforward use
- Hydrophobic bacterial filter for protection of the pump
- User-friendly accessories
- Mobile and portable
- For use in clinic and hospital



Applications

SENATOR LOW VACUUM is the ideal suction pump for all procedures where low vacuum is required.

Using the appropriate accessories **SENATOR LOW VACUUM** is the ideal suction pump for pleural drainage. It can be also used for wound drainage as well as for neuro surgical procedures.

Technical Data:

CE 0123

Suction capacity	15 liter/minute
Vacuum	up to 100mbar
Nominal voltage	230 Volts, 50/60Hz (115 Volts on request)
Nominal power/ power consumption	0.45A, 100 Watt (230V)
Dimensions	345 x 245 x 282 mm without trolley 1000 x 470 x 680 mm with trolley
Weight	7,4 kg without trolley 21,0 kg with trolley
Protection class	Protection class I, BF, IPX I
Tests/certificates	MDD 93/42 EC, EN 60601-1, EN60601-1-2, EN 10079-1, ISO 9001

This high quality Swiss product is guaranteed for 2 years.

Ardo medical AG
Gewerbstrasse 19
6314 Unterägeri
Switzerland
Tel. +41-(0)41 754 70 70
Fax +41-(0)41 754 70 71
info@ardo.ch
www.ardo.ch

